

Toward OAM-selective frequency conversion in a three-mode fiber

Afshin Shamshooli,¹ Cheng Guo,¹ Francesca Parmigiani,² Xiaoying Li,³ and Michael Vasilyev^{1*}

¹Department of Electrical Engineering, University of Texas at Arlington, Arlington, TX 76019, USA

²Microsoft Research, Cambridge, CB1 2FB, UK

³College of Precision Instruments and Opto-electronics Engineering, Key Laboratory of Opto-electronic Information Technical Science of Ministry of Education, Tianjin University, Tianjin, 300072, China

*E-mail: vasilyev@uta.edu

Abstract: We describe OAM-compatible mode-selective frequency conversion in a few-mode fiber and experimentally demonstrate downconversion of various superpositions of signal modes LP_{11a} and LP_{11b} to the same LP_{11b} mode with conversion efficiency differences <0.8 dB.

OCIS codes: (190.4410) Nonlinear optics, parametric processes; (190.4420) Nonlinear optics, transverse effects in; (060.4370) Nonlinear optics, fibers; (190.4380) Nonlinear optics, four-wave mixing.

Mode-division multiplexing promises increase in channel capacity of both classical and quantum communications [1], hereby bringing attention to multiplexers and demultiplexers of spatial modes. One of desired features of the mode demultiplexer is the dynamic reconfigurability of its mode basis. In classical transmission, such reconfiguration could reverse the mode mixing and relax the requirements on electronic processing of the received signals. In quantum key distribution, switching between mutually unbiased mode bases could increase the dimension of the Hilbert space used for encoding. In either case, low loss and low crosstalk of the demultiplexer are important. Not long ago, we have demonstrated such a demultiplexer in a two-mode LiNbO₃ waveguide [2, 3], where, by adjusting the spatial profile of a 1560-nm pump wave, we could selectively upconvert either mode TM₀₀, or mode TM₀₁, or any superposition of these two modes of a 1540-nm signal to TM₀₁ mode at 775 nm, for both classical [2] and single-photon-level [3] signals. More recently, we have demonstrated a scheme of similar functionality (mode demultiplexing by mode-selective frequency conversion) in a $\chi^{(3)}$ nonlinear medium, such as a few-mode fiber (FMF), based on a combination of two inter-modal four-wave mixing (IM-FWM) processes [4, 5]. Compared to LiNbO₃ platform, nonlinear FMFs can offer wider design options for mode- and dispersion-engineering and better mode match to the FMFs used in transmission links. IM-FWM in FMF has recently attracted attention for tunable wavelength conversion [6–8] and correlated photon-pair generation [10]. Our preliminary results [4] have shown good crosstalk performance (mode selectivity) for each of the two IM-FWM processes individually. In [5] we implemented both processes simultaneously and demonstrated their combined ability to handle any superposition of LP₀₁ and LP_{11a} modes in the two-mode signal space. In FMF-based links, however, it is important to demultiplex various mode superpositions from a group of degenerate modes (e.g., selecting orbital angular momentum, or OAM, mode from LP_{11a}, LP_{11b} mode space).

In this work we demonstrate such OAM-compatible mode-selective frequency conversion in LP_{11a}, LP_{11b} mode space. Our scheme employs a combination of two IM-FWM processes illustrated in Fig. 1a. We use an elliptical-core FMF [7] that supports three non-degenerate modes: LP₀₁, LP_{11a}, and LP_{11b}, to be referred to as three-mode fiber (TMF) below. In IM-FWM process 1, pumps 1 and 2 downconvert LP_{11a} signal to LP_{11b} output. In process 2, pumps 3 and 4 downconvert LP_{11b} signal to the same LP_{11b} output mode. With all 4 pumps present, a selected superposition (e.g., OAM) of signal LP_{11a} and LP_{11b} modes is downconverted, whereas the orthogonal mode superposition is left unperturbed. Selection of the mode superposition is done by choosing relative powers of the 2 pairs of pump waves (i.e., relative weights of processes 1 and 2) and pump phase difference $\Delta\phi = (\phi_{p1} - \phi_{p2}) - (\phi_{p3} - \phi_{p4})$. For each process, the phase-matching condition [10] requires equal group velocities at the average frequencies of the two waves present in each spatial mode. These average frequencies, converted to wavelengths, are shown by dashed lines in Fig. 1a. Figure 1b shows measured relative inverse group velocities (RIGV) $1/v_g$ of LP₀₁, LP_{11a}, and LP_{11b} modes of our TMF. The LP_{11a} and LP_{11b} curves are approximately parallel to the LP₀₁ curve and are horizontally shifted from it by ~ 24 nm ($\Delta v_1 = 3$ THz) and ~ 41 nm ($\Delta v_2 = 5.1$ THz), respectively. Thus, the phase matching is satisfied when the dashed lines in Fig. 1a are separated by 17 nm and 41 nm for processes 1 and 2, respectively. Energy conservation and phase matching put the following 4 constraints on the frequencies of the 6 involved waves: $v_{p2} - v_{p1} = v_{p4} - v_{p3} = v_s - v_{WC} = \Delta v_2 - \Delta v_1$ and $v_s = v_{p3} - \Delta v_1$, where v_s (or v_{p3}) and v_{p1} (or v_{p2}) can be chosen arbitrarily, and subscript “WC” stands for wavelength-converted output. In our experiment, we downconvert signal from 1583 nm to 1601.1 nm, using wavelengths 1558.3, 1541.1, 1560.1, and 1542.9 nm for pumps 1, 2, 3, and 4, respectively.

Figure 1c shows our experimental setup. All pumps and the signal are carved into 10-ns-long flat-top pulses with 10-MHz repetition rate by 3 intensity modulators. The pumps are then amplified by telecom-grade C-band erbium-doped fiber amplifiers (EDFAs). Pump 2 is converted to LP_{11a} mode by a phase plate PP1, combined with signal in free space by beam dichroic beam splitter DBS, and combined with LP₀₁-mode pumps 3 and 4 by free-space beam splitter BS1. Pump 1 is converted to LP_{11b} mode by a phase plate PP2, combined these 4 beams by BS2, and coupled into the 1-km-long TMF by an objective. The TMF output is split between an infrared camera and a single-mode fiber (SMF) connected to the optical spectrum analyzer (OSA), which in this case measures the LP₀₁ “output port” of the TMF. By

inserting phase plate PP4 or PP5 prior to SMF coupling, we can also measure LP_{11a} or LP_{11b} “output port” of the TMF. We can gradually vary the signal spatial mode from LP_{11a} to LP_{11b} by rotating the phase plate PP3 (when it is at 0°, it generates 100% LP_{11a} mode, and when it is at 90°, it generates 100% LP_{11b} mode; in the intermediate positions it generates various two-mode superpositions). To maximize IM-FWM, we co-polarize all three input waves in each process. Mode selectivity of each individual process is quantified by comparing conversion efficiency (CE) for the “desired” signal mode (LP_{11a} in process 1, LP_{11b} in process 2) to the CE for the “undesirable” signal mode (LP_{11b} in process 1, LP_{11a} in process 2). The gray and blue traces in Fig. 2a show the ratio of these two efficiencies (crosstalk) for process 2 to be 23.7 dB. Crosstalk for process 1 is similarly good (not shown in Fig. 2a).

Figure 2a also shows the LP_{11b} output port spectrum for simultaneous processes 1 and 2 (4 pumps present). Average powers inside the TMF are 0 dBm for the signal and 10.5, 5.5, 9, and 7 dBm for pumps 1, 2, 3, and 4, respectively. At these powers the CEs for processes 1 and 2 are nearly equal. If we had stable phase $\Delta\phi = (\phi_{p1} - \phi_{p2}) - (\phi_{p3} - \phi_{p4})$, we would have been able to select for wavelength conversion a superposition of LP_{11a} and LP_{11b} modes with a specific relative phase (e.g., $\Delta\phi = \mp\pi/2$ selects mode with OAM $l = \pm 1$). However, such stabilization (based on optical comb) has not been implemented in our setup yet, and our $\Delta\phi$ fluctuates randomly on 0.1–1 μ s scale. This means that we can observe mode-independent signal conversion to LP_{11b}, as both LP_{11a} and LP_{11b} components of any signal superposition are independently converted to LP_{11b} and added incoherently. This is illustrated in Fig. 2b, which shows nearly the same CEs (within 0.8 dB range from one another), measured for various signal superpositions with weight of LP_{11b} component ranging from 0 to 100%.




Fig. 1. (a) Two parametric processes, whose combination enables OAM-compatible mode-selective frequency conversion in the TMF. (b) Measured relative inverse group velocity (RIGV) data for the modes of our TMF. (c) Experimental setup.




Fig. 2. (a) Spectra at LP_{11b} port for process 2 alone (gray, blue) and processes 1, 2 combined (purple). (b) CE for various signal mode superpositions.

To summarize, we have simultaneously implemented two IM-FWM processes necessary for OAM-compatible mode-selective frequency conversion. We have shown that, in the absence of pump phase stabilization, this scheme produces mode-independent signal frequency conversion in LP_{11a}, LP_{11b} mode space. To increase CEs, one could employ high-power EDFAs and, possibly, a customized highly-nonlinear FMF with a reduced core size.

This work has been supported in part by the NSF grants ECCS-1937860 and ECCS-1842680.

References

- [1] D. J. Richardson *et al*, Nat. Phot. **7**, 354 (2013).
- [2] Y. B. Kwon *et al*, CLEO 2016, STh3P.4.
- [3] Y. B. Kwon *et al*, CLEO 2017, FF2E.1.
- [4] A. Shamshooli *et al*, CLEO 2020, SM3P.3.
- [5] A. Shamshooli *et al*, IPC 2020, ThF1.2.
- [6] O. F. Anjum *et al*, JLT **36**, 3678 (2018).
- [7] F. Parmigiani *et al*, OE **25**, 33602 (2017).
- [8] O. F. Anjum *et al*, OE **27**, 24072 (2019).
- [9] K. Rottwitz *et al*, Fibers **6**, 32 (2018).
- [10] R.-J. Essiambre *et al*, PTL **25**, 539 (2013).